PratiKa wander socket - straight -16 A - 3P + N + E - 380...415 V AC -**IP44**

PKY16M435

Range	PratiKa
Product or component type	Wander socket
Device short name	PratiKa fast
Plug, socket category	Low voltage
Poles description	3P + N + E
Network type	AC
Outlet standard	Industrial

Complementary	
Plug, socket, control station shape	Straight
[In] rated current	16 A
[Ue] rated operational voltage	380415 V
Network frequency	50/60 Hz
Ground lug clockwise position	6 h
Plug, socket material	Housing: self-extinguishing engineering polymer
Contacts material	Sleeves: brass
Connections - terminals	Fast connection
Cable cross section	12.5 mm²
Cable outer diameter	815 mm
Cable entry	Fair lead Cable gland
Thread type	Pg 21
Net weight	0.241 kg
Height	97 mm
Width	97 mm
Depth	153 mm
Colour	Grey (RAL 7035)
Voltage colour	Red

Environment

Ambient air temperature for operation	35 °C (86400 s) -2540 °C
Relative humidity	50 % at 40 °C 70 % at 30 °C 90 % at 20 °C
Fire resistance	850 °C conforming to IEC 60695-2-1
IK degree of protection	IK08 conforming to EN 62262
IP degree of protection	IP44 conforming to IEC 60529
Standards	IEC 60309-2 IEC 60309-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	216.0 g
Package 1 Height	6.2 cm
Package 1 width	9.5 cm
Package 1 Length	16.3 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	2.318 kg
Package 2 Height	17 cm
Package 2 width	27 cm
Package 2 Length	27 cm
Unit Type of Package 3	S03
Number of Units in Package 3	20
Package 3 Weight	5.14 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

REACh Declaration
Compliant EU RoHS Declaration
Yes
Yes
China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------